



Cixi Kent Bearing Co., Ltd.



3.938 Inch | 100.025 Millimeter x 3.39 Inch |
86.106 Millimeter x 4.25 Inch | 107.95 Millimeter
SKF FSYE 3.15/16 NH Pillow Block Bearings

Bearing No. FSYE 3.15/16 NH

FSYE 3.15/16 NH Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	22.47
EAN	7316577103840
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Stepped Sleeve
Housing Style	4 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	22220
Seals	Trigard
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Double Row Heavy Duty Locating Bearing Open End With Grub Screw
Long Description	4 Bolt Pillow Block; 3-15/16" Bore; 4-1/4" Base to Center Height; Stepped Sleeve Mount; Spherical



Cixi Kent Bearing Co., Ltd.

	Roller Bearing; 12" Minimum Bolt Spacing; 13" Bolt Spacing Maximum; Relubricatable
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	FSYE 3.15/16 NH
Weight / LBS	49.5
Bolt Spacing Maximum	13 Inch 330.2Millimeter
B	4.25 Inch 107.95 Millimeter
Nominal Bolt Center to Center	12.5 Inch 317.5 Millimeter
d	3.938 Inch 100.025 Millimeter
Bolt Spacing Minimum	12 Inch 304.8Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
D	3.39 Inch 86.106 Millimeter
bore diameter:	3.9375 in
bolt center-to-center length:	12-1/2 in
overall length:	15.2500 in
base width:	4-1/2 in
overall height:	8.5625 in
expansion type:	Non-Expansion Bearing (Fixed)
mounting:	Four-Bolt Base
finish/coating:	Uncoated
bearing type:	Spherical Roller
seal type:	Tri-Guard



Cixi Kent Bearing Co., Ltd.

bore type:	Round
radial dynamic load capacity:	95000 lbf
housing construction:	Solid Pillow Block
radial static load capacity:	110000 lbf
base to bore centerline:	4.2500 in
maximum rpm:	1250 RPM
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	FSYE
locking device:	Concentric Collar
replacement bearing:	22220